[轉貼]PHP 推撥 IOS PUSH
作者是 Administrator
週四, 25 四月 2013 16:22 - 最近更新 週四, 25 四月 2013 16:26

文章轉貼自:http://blog.csdn.net/newjueqi/article/details/8315093

是按照教程http://blog.csdn.net/newjueqi/article/details/7898591 來做的。

注意事項：

1. 測試階段使用的推送地址：

ssl://gateway.sandbox.push.apple.com:2195

正式上線使用的推送地址：

ssl://gateway.push.apple.com:2195

2.那裡給的php推送代碼有問題，下面我貼出修改後推送成功的代碼：

[php] view plain copy

```
<?php


// □□□□□□□□□□□deviceToken□□□□□□□□□□□□□□□□
$deviceToken=$_POST['deviceToken'];

// Put your private key's passphrase here:
$passphrase = 'password';

// Put your alert message here:
$message = $_POST['message'];

$ctx = stream_context_create();

stream_context_set_option($ctx, 'ssl', 'local_cert', 'ck.pem');
stream_context_set_option($ctx, 'ssl', 'passphrase', $passphrase);

// Open a connection to the APNS server
//□□□□□□□□□□□
//$fp = stream_socket_client('ssl://gateway.push.apple.com:2195', $err, $errstr, 60,
STREAM_CLIENT_CONNECT, $ctx);
//□□□□□□□□□□□□□□appstore□□□□□□
$fp = stream_socket_client('ssl://gateway.sandbox.push.apple.com:2195', $err,$errstr,
60, STREAM_CLIENT_CONNECT|STREAM_CLIENT_PERSISTENT,
$ctx
);


if (!$fp){
exit("Failed to connect: $err $errstr" . PHP_EOL);
}

//echo 'Connected to APNS' . PHP_EOL;
// Create the payload body

$body['aps'] = array(
'alert' => $message,
'forum_id' => 88,
'topic_id' => 999,
);

// Encode the payload as JSON
$payload = json_encode($body);
```

```
41.
42.  // Build the binary notification
43.  //$msg = chr(0).pack('n', 32).pack('H', $deviceToken). pack('n',
strlen($payload)).$payload;
44.  $msg = chr(0) . pack("n",32) . pack('H*', str_replace(' ', '', $deviceToken)) . pack("n",strl
en
(
$payload
)) .
$payload
;

45.
46.  // Send it to the server
47.  $result = fwrite($fp, $msg, strlen($msg));
48.
49.  if (!$result){
50.   echo 'Message not delivered' . PHP_EOL;
51.  }else{
52.   echo 'Message successfully delivered' . PHP_EOL;
53.  }
54.
55.  // Close the connection to the server
56.  fclose($fp);
57.
58.  ?>
```