osCommerce[illegible]

[illegible] Administrator
[illegible], 09 [illegible] 2009 16:44 - [illegible] [illegible], 09 [illegible] 2009 17:03

[illegible]osCommerce[illegible],[illegible],[illegible] [illegible],[illegible],[illegible],[illegible],[illegible] ,[illegible]DEBUG[illegible]。

[illegible]PHP[illegible] orders_total [illegible]account.php[illegible]

[illegible] $orders_query = tep_db_query("select o.orders_id, o.date_purchased, o.delivery_name, o.delivery_country, o.billing_name, o.billing_country, ot.text as order_total, s.orders_status_name from " . TABLE_ORDERS . " o, " . TABLE_ORDERS_TOTAL . " ot, " . TABLE_ORDERS_STATUS . " s where o.customers_id = '" . (int)$customer_id . "' and o.orders_id = ot.orders_id and ot.class = 'ot_total' and o.orders_status = s.orders_status_id and s.language_id = '" . (int)$languages_id . "' order by orders_id desc limit 3");

[illegible]o.orders_id = ot.orders_id and ot.class[illegible]checkout_process.php
[illegible]

[illegible] for ($i=0, $n=sizeof($order_totals); $i $insert_id,
[illegible]'title' => $order_totals[$i]['title'],
[illegible] 'text' => $order_totals[$i]['text'],
[illegible]'value' => $order_totals[$i]['value'],
[illegible] 'class' => $order_totals[$i]['code'],
[illegible] 'sort_order' => $order_totals[$i]['sort_order']);
[illegible] tep_db_perform(TABLE_ORDERS_TOTAL, $sql_data_array);

}

[illegible]
$order_totals[illegible]LINUX[illegible]WINDOWS[illegible]。