

```
session.php
```

□ □ □ □ □ □ □ □ ○

□□□□□□□□ session。 □□□□□□□□

1. php.ini

php session files 。 “session.save_handler = files” “files” “User”。

```
session = Session()
```

2.□□□□□□

```
CREATE TABLE `db_session` (  
  `sesskey` char(32) NOT NULL,  
  `expiry` int(11) unsigned NOT NULL,  
  `value` text NOT NULL,  
  PRIMARY KEY (`sesskey`)  
) ENGINE=InnoDB DEFAULT CHARSET=latin1;
```

[/code]

```
□□□□□□ db session
```

```
sesskey expiry value sesskey
```

Value of session 。

3. session mysql.php。 session。 session。

session_mysql.php

PHP:

:

<?php

\$gb_DBname = "db_myBBS"; //

\$gb_DBuser = "root"; //

\$gb_DBpass = "23928484"; //

\$gb_DBHOSTname = "localhost"; // IP

\$SESS_DBH = "";

\$SESS_LIFE = get_cfg_var("session.gc_maxlifetime"); // session 。

function sess_open(\$save_path, \$session_name)

{

global \$gb_DBHOSTname, \$gb_DBname, \$gb_DBuser, \$gb_DBpass, \$SESS_DBH;

if (!\$SESS_DBH = mysql_pconnect(\$gb_DBHOSTname, \$gb_DBuser, \$gb_DBpass)) {

echo "MySql Error:" . mysql_error() . "";

die();

}

if (!mysql_select_db(\$gb_DBname, \$SESS_DBH)) {

echo "MySql Error:" . mysql_error() . "";

die();

}

return true;

}

```
function sess_close()

{

return true;

}

function sess_read($key)

{

global $SESS_DBH, $SESS_LIFE;

$qry = "select value from db_session where sesskey = '$key' and expiry > " . time();

$qid = mysql_query($qry, $SESS_DBH);

if (list($value) = mysql_fetch_row($qid)) {

return $value;

}

return false;

}

function sess_write($key, $val)

{

global $SESS_DBH, $SESS_LIFE;

$expiry = time() + $SESS_LIFE;

$value = $val;

$qry  = "insert into db_session values('$key',$expiry,'$value')";

$qid  = mysql_query($qry, $SESS_DBH);

if (!$qid) {

$qry = "update db_session set expiry=$expiry, value='$value' where sesskey='$key' and expiry > " . time();
```

```
$qid = mysql_query($qry, $SESS_DBH);

}

return $qid;

}

function sess_destroy($key)

{

global $SESS_DBH;

$qry = "delete from db_session where sesskey = '$key'";

$qid = mysql_query($qry, $SESS_DBH);

return $qid;

}

function sess_gc($maxlifetime)

{

global $SESS_DBH;

$qry = "delete from db_session where expiry < " . time();

$qid = mysql_query($qry, $SESS_DBH);

return mysql_affected_rows($SESS_DBH);

}

session_module_name();

session_set_save_handler("sess_open", "sess_close", "sess_read", "sess_write",
"sess_destroy", "sess_gc");

?>
```

4.。 session_mysql.php。 session_test.php PHP: :

```
<?php
```

```
include("session_mysql.php");
```

```
session_start();
```

```
$_SESSION['abc'] = "A: I will be back!";
```

```
$_SESSION['meto'] = "B: Me too ";
```

```
$_SESSION['name'] = "louis ";
```

```
echo "<a href='get_session_test.php'>click me</a>";
```

```
?>
```

```
get_session_test.php : <?php include("session_mysql.php"); session_start(); ec  
ho $_SESSION['abc'];
```

```
echo "<br>";
```

```
echo $_SESSION['meto'];
```

```
echo "<br>";
```

```
echo $_SESSION['name'];
```

```
$_SESSION['wq'] = "12e";
```

```
echo "<br><a href='get_session_test2.php'>click again</a>";
```

```
?>
```

```
get_session_test2.php : <?php include("session_mysql.php"); session_start(); e  
cho $_SESSION['abc'];
```

```
echo "<br>";
```

```
echo $_SESSION['meto'];
```

```
echo "<br>";
```

```
echo $_SESSION['name'];
```

```
echo "<br>";
```

```
echo $_SESSION['wq'];
```

```
//session_destroy();// session
```

```
?>
```